




Our individual Safety Pallet Load Gates are the safest way to raise loads onto Mezzanine Platforms



With over 30yrs
experience supplying
and installing Safety
Pallet Load Gates,
Racking UK offer a wide
range of standard and
non-standard loading
gates to suit all sizes of
Pallets.

The non-standard gates cater for situations where there is limited headroom and depth, where high and deep pallets are to be loaded onto platforms, and when a shutter door is spaced back from the platform.

RUK 1500

This is a one width pallet gate to suit maximum pallet dimensions of 1500mm high x 1450mm deep x 1300mm deep. The outer width is 1600mm and will work with a headroom of 2100mm.



RUK 1625

This pallet gate can be used on multi-tier mezzanine floors as the arms do not protrude over the platform edge when in either the open or closed positions. A mesh panel can also be attached to the front gate.

The RUK 1625 pallet gate will take maximum pallet dimensions of 1625mm high x 1450mm deep. The outer width varies between 1600mm – 3000mm and will work in a headroom of 2100mm. This pallet gate can also be modified to accommodate higher pallets.



This pallet gate can be used for pallet dimensions of 1650mm high x 1450mm deep. The outer width varies between 1600mm – 3000mm and will work in a headroom of 2100mm.



Click the model numbers for an animated demonstration





Based in Chelmsford, Essex, we provide our high quality storage equipment and services to commercial and industrial customers from across Essex, Kent, London and the West Midlands.

As one of Essex's leading storage and workplace equipment specialists, we are confident that we will be able to provide you with the ultimate solution, no matter how challenging the requirements.

IMPROVED STORAGE AND MATERIALS HANDLING MEANS ADDITIONAL PROFIT


THERE REALLY IS NO OTHER WAY TO LOOK AT IT!

01621 786630

Suite 340
Dorset House
25 Duke St. Chelmsford CM1 1TB
E-mail: essexmezz@gmail.com
www.racking-uk.com

RUK MODEL 12LL

This pallet gate can be used when the available height on the platform edge is lower than at the back or when the headroom across the platform is less than 2100mm. Pallet heights will vary depending on the available headroom. The outer width varies between 1600mm – 3000mm.



RUK MODEL 30

This gate can be used when there are restrictions on the depth of the platform. The main advantage with this pallet gate is that when the front gate is in the closed position the floor area around the gate is clear, allowing for the pallet to be removed in three directions.

RUK MODEL 30M

This pallet gate is the same as the Model 30 except that it can be modified to take deeper and lower pallets.


RUK LC/HP


This pallet gate can be used on multi-tier mezzanine floors as the arms do not protrude over the platform edge when in either the open or closed positions.



The standard pallet gates will accommodate pallet

heights of 1800mm – 2400mm with a pallet depth of 1450mm and 2600mm high with a pallet depth of 1650mm. The outer width varies between 1600mm – 4500mm.





Click the model numbers for an animated demonstration

